



## STANDARD VOLTAGE FOR A SIMPLE INSTALLATION



- HIGH EFFICIENCY, 16 SEER / 9 HSPF
- SLEEK LOOK TO BLEND WITH YOUR DECOR
- PRECISE AIRFLOW CONTROL
- WIFI INCLUDED

### A SIMPLE, ECONOMICAL AND EFFICIENT SOLUTION.

Slim, stylish and elegant, the Livo+ Wall Mount units are an economical installation alternative with just 115V required for electrical hook-up. These 16 SEER / 9 HSPF heat pump systems are built around GREE's variable speed compressor technology, using eco-friendly R410A refrigerant.



- G10 inverter technology
- I-Feel function
- Multiple fan speeds
- Sleep function
- Acrylic resin coil coating
- Dehumidification
- Intelligent preheating
- Automatic voltage adaption
- Low voltage start-up
- Self-Diagnosis
- Swing louver control
- LED display settings
- Privacy lock mode
- Cooling range:  
0°F - 115°F
- Heating range:  
-4°F - 75°F
- Washable, polymeric  
air filters
- Advanced filter options

MODEL		LIVS09HP115V1B	LIVS12HP115V1B
System Type		HEAT PUMP	
<b>SYSTEM PERFORMANCE</b>			
Cooling Capacity (Min-Max)	Btu/h	9000 (2764 - 10918)	12000 (3753 - 12500)
Heating Capacity (Min-Max)	Btu/h	9600 (2081 - 12283)	13000 (3412 - 15013)
SEER / EER		16 / 10.05	16 / 10.05
HSPF / COP		9 / 3.3	9 / 3.05
Energy Star®		NO	
Cooling Temperature Range	*F	0 - 115	0 - 115
Heating Temperature Range	*F	-4 - 75	-4 - 75
<b>INDOOR UNIT</b>			
		LIVS09HP115V1BH	LIVS12HP115V1BH
Air flow (Min-Max)	CFM	171 - 318	194 - 400
Sound Pressure Level (Cooling / Heating)	dB(A)	28 - 42 / 28 - 42	29 - 43 / 29 - 43
Dehumidification	pt/hr	1.69	2.96
Condensate Drain Size (OD)	in	5/8	5/8
Unit Dimension (WxHxD)	in	31 1/8 x 10 13/16 x 7 7/8	33 5/16 x 11 7/16 x 8 3/16
Package Dimension (WxHxD)	in	34 x 13 7/8 x 10 5/8	36 1/8 x 14 5/16 x 11
Weight (Net / Gross)	lbs	20 / 24.25	22 / 27.6
<b>OUTDOOR UNIT</b>			
		LIVS09HP115V1BO	LIVS12HP115V1BO
Compressor Type		GREE G-10 / 2 - STAGE / 3 CYLINDER INVERTER	
Sound Pressure Level (Cooling / Heating)	dB(A)	53 / 53	53 / 53
Unit Dimension (WxHxD)	in	33 7/16 x 21 1/4 x 12 5/8	33 7/16 x 21 1/4 x 12 5/8
Package Dimension (WxHxD)	in	34 5/8 x 22 13/16 x 14 3/16	34 5/8 x 22 13/16 x 14 3/16
Weight (Net / Gross)	lbs	62.8 / 68.4	67.25 / 72.8
Refrigerant Charge - R410A	oz	24.7	31.8
Coil Type		Aluminum Fin-Copper Tube / Acrylic Resin Protection	
<b>REFRIGERANT PIPING</b>			
Line Set Size (Liquid - Gas)	in	1/4 - 3/8	1/4 - 3/8
Pre-Charge Length	ft	25	
Pipe Length (Min / Max)	ft	10 / 49	10 / 66
Max. Pipe Elevation	ft	33	33
<b>ELECTRICAL</b>			
Power Supply		115V / 1Ph / 60Hz	
Rated Current Cooling	amps	11.27	13
Rated Current Heating	amps	10.65	13.2
MCA	amps	17	20
MOCP	amps	25	30
Main Power Wire Size	AWG	Per Local Code	
Interconnecting Wire Size	AWG	14 / 4	
LIMITED WARRANTY		5 Years Parts and Compressor - Residential	