

Submittal Data: XE71	XE71 Wired Programmable Controller
Job Name	Location Date
Purchaser	Engineer
Submitted To	For Construction Approval Construction
Unit Designation	Schedule No.
GENERAL FEATURES - Tactile Feedback Keypad - Easy Setup and Programming - Sleek Thin Design Blends into any Décor - Ready to use cable included. (Reaches up to 26 feet) - Convenient LCD Display Backlighting - No Batteries Required - 115V or 230V Single Zone Compatible - Built in RF Remote Control Receiver - NOT able to set static pressure on DUCT B series, use XK76 or XK19	XE71 Image: Sector Se
Compatible with the following Models:	
Indoor Models	Model Numbers
Livo Series	xLIVxxxHPxxxV1xH

xLIVxxxHPxxxV1xH
VIRxxHPxxxV1xH
VIRUxxHP230V1xH
SAPxxHP230V1AH
DUCTxxHP230V1AD
CASxxHP230V1xC
FLRxxHP230V1xF

XE71 Command Center allows fast & easy access to a large number of functions. The following is a list of typical features and functions supported by the XE71 controller:

Note: Some indoor models may not support specific system features or functions.

Always refer to the indoor unit Owner's Manual for a complete list of feature and functions.

On/Off - The On/Off button allows you to start and stop the system.

Operating Mode - Allows users to select an operating mode (i.e. Cooling, Heating, Dry, and Fan Only).

Fan Speed -The indoor fan (i.e. High, Medium, Low & Auto) can be adjusted for peak comfort and quietness.

Room Setpoint – Adjust room setpoint temperature between 61 deg F to 86 deg F (16 ~ 30 range).

Timer Mode - Program a time period (i.e. 0.5-24 hr.) to which the system will turn ON or OFF.

Sleep Mode – Automatically adjust room temperature during your sleep time (i.e. 0.5-24 hr. range).

Turbo Mode – Turbo will force system to run at higher speeds to reach the desired room temperature faster.

X-Fan Mode - Removes moisture build up on coil when the system is turned OFF to prevent mold and mildew. **Privacy Lock** - Privacy Lock to prevent unauthorized access to the controls and tampering with system settings.

