

GREE		Multi-Room Ductless systems		
Submittal Data: CAS24HP230V1AC		24,000 BTU/H Ceiling Cassette		
Job Name		Location Date		
Purchaser		Engineer		
Submitted To		For Reference	Approval Construction	
Unit Designation		Schedule No.		
GENERAL FEATURES				
-Quiet Operation -Multi-Speed Fan				
-4-way Discharge Air				
-Internal Condensate Drain Pump				
-Swing Louver				
-Both Wireless & Wired Remote Control	lers			
-Power Failure Recovery -Sentry Condensate Overflow Protectio	ın.			
-Decorative Grille (Required / Sold Separately)				
CASGRILLE1LG		22	Contribution & Fas. Made	
-Limited 5 yr. Parts Warranty (Residential Only)			Fatibles V Train Davide	
System Rat		Units Specifica	tion & Data	
Cooling*				
Rated Capacity	22,800 BTU/H			
		Wired Controller	XK19	
Heating*				
Rated Capacity	27,400 BTU/H	Air Filter	Netted polypropylene	
Sound Pressure (Hi/Lo)**		Condensate Drain Lift (Height)	12-in	
Cooling	49/45 dbA	Condendate Brain Ent (Florgitt)	305-mm	
Heating	49/45 dbA	Drain Size (OD)	1.2-in	
		,	31-mm	
Air Flow (min/max)				
Indoor Fan	500/694 CFM			
Electrical Ratings		Refrigerant Piping Data		
Fan Motor		Refrigerant Type	R410A	
Output Power	50 W			
FLA	0.4 A	Gas Pipe Size (OD)	5/8-in	
Power Supply		Liquid Pipe Size (OD)	3/8-in	
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz	Liquid Fipe Size (OD)	3/0-111	
Voltage Range	187 - 253 V	Connection Method	Flared	
MCA	1.0 A	Somiosasii iiloaloa	Tidicu	
Interconnecting Cable Wire Size	14-4 AWG			
		* Test conditions are based on AHRI 210/2	240.	
		**Sound Power ratings are per AHRI 270 a		
R45107A	AUDI	CERTIFIED ~	RTIFIED	
near asses-depleting refrigerant	7.2	ww.ahridirectory.org	CIOTE OF	

DIMENSIONAL SPECIFICATIONS

CAS24HP230V1AC


24,000 BTUH MODEL


Model # CAS24HP230V1AC 24,000 BTUH 230V

Decorative Grille (Required / Sold Separately)

CASGRILLE1LG

Units: inch (mm)





Ø1.0 (25)

11.6 (294)

10.0 (255)

2.0 (52)

(Part of the content of the content

Note: Size refrigerant lines based on evaporator port sizes.


Installation stands for main body of the unit

Abo

62/78 lbs

Weight (Net/Gross)

MINIMUM CLEARANCES



Notes

- 1. Recommended Interconnecting Cable Type Stranded Bare Copper Conductors THHN 600V Unshielded Wire
- 2. Power wiring cable size must comply with applicable national and local codes.
- 3. Test conditions are based on AHRI 210/240.

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All rights reserved.