

SYSTEM FEATURES

- · Full DC Inverter Technologies.
- · Can Connect up to 10 Indoor Units.
- · Intelligent Temperature Control Technology.
- · Oil Balance Control Technology.
- · CAN Bus Network Technology.
- \cdot Factory Tested up to 48°C/118°F Ambient.
- · Ultra Long Piping Run up to 984 ft.
- · Automatic Address Setting.
- · Small Installation Space.

OUTDOOR UNIT FEATURES

- · Low Noise Design with DC Fan Motor.
- · Advance Torque Control Technology.
- · Sensorless DC Inverter Fan Motor.
- \cdot High Efficiency Digital PFC Control.
- · Wider Operation Condition Range.
- · Compressor Oil Storage Technology.
- · Two Stage Oil Separation Technology.
- · Automatic Fault Detection.















SPECIFICATIONS:

AHRI CERTIFIED.

VIN.

MODEL			GMV-24WL/C-T-(U)	GMV-28WL/C-T-(U)	GMV-36WL/C-T-(U)	GMV-48WL/C-T-(U)	GMV-60WL/C-T-(U)
Capacity Range Ton		Ton	2	2.5	3	4	5
Capacity	Cooling	Btu/h	24,000	28,000	37,500	48,000	60,000
	Heating	Btu/h	28,000	30,000	42,000	54,000	64,000
Air Flow Volume		CFM	2,295	2,295	3531	3,708	4,590
Power Supply		V/Ph/Hz	208/230 / 1 / 60				
	Cooling	°F	23°F - 118°F				
	Heating	°F	-4°F - 81°F				
MCA		А	21	21	28.5	33	34.5
МОР А		А	25	30	35	40	40
Maximum IDU per unit Un		Unit	4	4	7	8	10
Refrigerant Charge Volume		lbs.	5.3	5.3	7.3	7.3	10.1
Sound Pressure Level		db(A)	57	57	55	55	63
Connecting Pipe	Liquid	in.	3/8	3/8	3/8	3/8	3/8
	Gas	in.	5/8	5/8	5/8	5/8	3/4
Dimension (WxDxH)	Unit	in.	38-9/16 x 14-3/16 x 31-1/8	38-9/16 x 14-3/16 x 31-1/8	35-3/8 x 13-3/8 x 53	35-3/8 x 13-3/8 x 53	37 x 12-5/8 x 56-1/4
	Package	in.	43-3/16 x 18-3/4 x 36-7/8	43-3/16 x 18-3/4 x 36-7/8	39-1/4 × 18 × 59-1/16	39-1/4 × 18 × 59-1/16	40-7/8 x 17-1/4 x 62-1/4
Net Weight/Gross Weight lbs.		176/198	176/198	246/273	246/273	273/299	
EER (Ducted/Non-Ducted)			11.0 /11.0	11.0 /11.0	11.5 /11.5	11/11.5	10.5/11
SEER (Ducted/Non-Ducted)			18.0/18.0	18.0/18.0	19.5/22	19.5/22	19.5/21
AHRI Certification No. (Ducted)			202242130	202541562	206335356	206335357	206335358
AHRI Certification No. (Non-Ducted)			204344210	204344211	206335353	206335354	206335355



360° Air Flow Cassette



Four Way Cassette



Two Way Cassette



One Way Cassette







Medium Static Ducted



 $\mathsf{High}\;\mathsf{Static}\;\mathsf{Ducted}$



Console



High Wall



Multi-Position Air Handler

CONTROLLERS:



Centralized Controller



Wired Controller Standard on Ducted Units



Wireless Controller Standard on Ductless Units



XK-55 Touch Screen Programmable Wired Remote Control



XK-86 Programmable Wired Remote Control



TO LEARN MORE ABOUT GREE PRODUCTS VISIT US AT: WWW.GREECOMMERCIAL.COM



Distributed by: