


Wired Controller Compatibility Chart



Wired Controller Series	Part Code	Description	Sapphire	All Vireo & Vireo ULTRA	All Vireo	Crown & Crown+	Terra
XE71	MC20700970	Single/Multi zone programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓		✓
XK41 (Obsolete) (Replaced by XE71)	GREEMC207059	Single/Multi zone High-Wall programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓		✓
XK76	MC20700360	Single/Multi zone programmable controller with touch pad & back light. Includes (1) 26 ft. & (1) 6.5 in. harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	✓	✓		✓



Wired Controller Series	Part Code	Description	Multi Cassette	Multi Slim Duct	Multi Floor/Ceiling	Mini-Console	U-Match Cassette	All U-Match Slim Duct	Floor/Ceiling U-Match	Mini-Console U-Match
XK19	MC20700140	Used with all Multi Zones - programmable controller with touch buttons. Includes 26 ft. wire harness Part # 40010232 with Molex plugs.	✓	✓	✓					
XE71 ^{1&2}	MC20700970	May be used with all Multi Zones: Cassette, Floor-Ceiling, Slim Duct models - programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓					
XE72 ^{1&2}	MC20701210	WIFI for all Multi Zones: Cassette, Floor-Ceiling, Slim Duct models - programmable controller with touch pad & back light. Includes (1) 26 ft. & (1) 6.5 in. harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	✓	✓					
XK41 (Obsolete) (Replaced by XE71)	GREEMC207059	May be used with all Multi Zones-Cassette, Floor-Ceiling, Slim Duct models- programmable controller with touch pad & back light. Includes 26 ft. wire harness Part # 4003800101 with Molex plugs.	✓	✓	✓					
XK76 ³	MC20700360	Single/Multi zone high wall programmable controller with touch pad. Includes (1) 26 ft. & (1) 6.5 in. wire harness Part # 4003800101 & 4001024512 with Molex plugs.	✓	DUCT B ²	✓					
XK60 ⁴	MC20700550	U-Match & U-Match+ programmable controller with buttons & back light. Requires field supplied 18/2 AWG 300V [min] stranded wire. Max effective wire length is 26 ft.					✓	✓	✓	



- Note: All Wired Controller wire harness is 26 ft., 26 ft. is the maximum length for effective operation. It should not be cut or spliced.
- XE71 May be used in lieu of the XK19, but, if used to replace an XK19 already installed the wire harness must also be replaced.
 - XE 71 & 72 have integrated control capability for up to 16 units, requires connection to a Smart Zone Controller.
 - XK76 Used with DUCT B models can be used to set external static pressure.
 - XK60 Can be used with UMAT BD hi-static duct models to set external static pressure.

* REPRESENTATIVE IMAGES, ACTUAL PRODUCT MAY VARY. CHECK SALES LITERATURE.
Go to GreeComfort.com <https://www.greecomfort.com/resources/dealer-resources-current-product/>, see **Wired Programmable Controllers** Section for more information.