



SUBMITTAL DATA: 3VIR12HP115V1A      12000 BTU/H Wall Mounted Heat Pump System		
Job Name	Location	Date
Purchaser	Engineer	
Submitted To	For	
Unit Designation	Schedule No.	

**YAP1F7F                                      3VIR12HP115V1AH                                      3VIR12HP115V1AO**



XE71 (Optional)

**GENERAL FEATURES**

- AHRI Certificate: 206839102**
- High Efficiency DC Inverter Technology**
- Compact and Quiet Design**
- Auto-Clean Function on Indoor Unit**
- Wireless Remote with LCD Display**
- Wired Controller Options**
- Wi-Fi Included (Factory Installed)**
- Low Ambient Cooling down to -13°F (Range -13°F to 122°F)**
- Low Ambient Heating down to -22°F (Range -22°F to 86°F)**
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin\*<sup>2</sup>**
- \* (Blue Fin) 500 Hrs Salt Spray Tested**

**5 Year Limited Compressor & Parts Warranty (Residential Only)**

## SPECIFICATIONS

## 3VIR12HP115V1AO / 3VIR12HP115V1AH

System Type		HEAT PUMP	
SYSTEM PERFORMANCE			
Cooling	Rated Capacity @ 95°F	Btu/h	12100
	Min-Max Capacity	Btu/h	3071 - 13400
	Rated Power Input (Min - Max)	W	220 - 1400
Heating	Rated Capacity @ 47°F	Btu/h	12100
	Rated Capacity @ 17°F	Btu/h	7700
	Min-Max Capacity	Btu/h	3071 - 15500
	Rated Power Input (Min - Max)	W	220 - 1500
SEER / EER		25 / 13	
HSPF / COP		11.5 / 3.61	
Energy Star®		YES	
Cooling Temperature Range		°F	-13 - 122
Heating Temperature Range		°F	-22 - 86
INDOOR UNIT		3VIR12HP115V1AH	
Fan Motor Output Power		W	15
Fan Motor FLA		amps	0.3
Air Flow (Min - Max)		CFM	230 - 400
Sound Pressure Level (Cooling / Heating)		dB(A)	20 - 43
Dehumidification		pt/hr	2.96
Condensate Drain Size (OD)		in	5/8
Unit Dimension (WxHxD)		in	32 1/2 x 11 1/2 x 7 3/4
Package Dimension (WxHxD)		in	34 1/4 x 11 3/4 x 10 1/8
Weight (Net / Gross)		lbs	20.9 / 25.4
OUTDOOR UNIT		3VIR12HP115V1AO	
Compressor Type		Rotary Inverter	
Compressor RLA		amps	15
Fan Motor Output Power		W	30
Fan Motor RLA		amps	0.5
Sound Pressure Level (Cooling / Heating)		dB(A)	54
Unit Dimension (WxHxD)		in	35 3/8 x 16 7/16 x 14 7/8
Package Dimension (WxHxD)		in	37 3/16 x 16 1/2 x 25 3/8
Weight (Net / Gross)		lbs	87.1 / 93.7
Refrigerant Charge - R410A		oz	47.3
Coil Type		Copper Tube / Aluminum Fin	
REFRIGERANT PIPING			
Line Set Size (Liquid - Gas)		in	1/4 - 1/2
Pre-Charge Length		ft	25
Pipe Length (Min - Max)		ft	10 - 66
Max. Pipe Elevation		ft	33
ELECTRICAL			
Power Supply (Voltage Operating Range)		115V / 1PH / 60HZ	
Rated Current (Cooling / Heating)		amps	12.45 / 13.1
MCA / MOCP		amps	21 / 30
Main Power Wire Size		AWG	Size Per Local Code
Interconnecting Wire Size		AWG	14 / 4
LIMITED WARRANTY			

**EXTENDED RATINGS**

**3VIR12HP115V1AO / 3VIR12HP115V1AH**

COOLING PERFORMANCE						HEATING PERFORMANCE				
Outdoor Ambient Temperature (DB)		Return Air Temperature				Outdoor Ambient Temperature (DB)		Return Air Temperature		
		80°F (DB)						70°F (DB)		
		TC (Btu/h)	SHR	EER	Power Input (W)			TC (Btu/h)	COP	Power Input (W)
<b>MAX OUTPUT</b>	-13°F	5530	3959	3.23	502	<b>MAX OUTPUT</b>	-22°F	4800	1.38	1019
	-10°F	5680	4084	3.24	513		-20°F	4980	1.41	1033
	-5°F	5840	4217	3.25	526		-15°F	5160	1.44	1048
	0°F	6000	4350	3.26	539		-10°F	5460	1.51	1062
	5°F	6240	4555	3.33	550		-5°F	5760	1.57	1077
	10°F	6420	4703	3.33	567		0°F	7800	2.09	1096
	15°F	6600	4851	3.32	583		5°F	9000	2.36	1116
	20°F	6900	5090	3.35	605		10°F	9600	2.61	1077
	25°F	7200	5328	3.37	627		15°F	10140	2.77	1072
	30°F	7680	5722	3.41	660		17°F	10680	2.93	1067
	35°F	8040	6011	3.43	688		20°F	10800	3.11	1019
	40°F	8400	6300	3.44	715		25°F	10920	3.23	989
	45°F	8760	6593	3.32	776		30°F	11160	3.34	980
	50°F	9120	6886	3.20	836		35°F	11280	3.47	955
	55°F	9420	7136	3.22	858		40°F	11400	3.59	931
	60°F	9720	7387	3.24	880		45°F	11760	3.63	951
	65°F	10380	7916	3.26	935		47°F	11880	3.63	960
	70°F	11040	8446	3.27	990		50°F	12000	3.63	970
	75°F	12120	9332	3.40	1045		55°F	12960	3.80	999
	80°F	12600	9735	3.48	1062		60°F	13800	3.93	1028
	85°F	13080	10137	3.56	1078		65°F	13200	3.66	1057
	90°F	12540	9749	3.38	1089		70°F	12720	3.49	1067
	95°F	12000	9360	3.20	1100		75°F	11880	3.23	1077
	100°F	11400	8919	2.93	1144		80°F	11160	3.12	1048
105°F	10800	8478	2.66	1188	86°F	10360	2.91	1044		
110°F	10440	8221	2.50	1227						
115°F	10080	7963	2.34	1265						
120°F	9480	7511	2.19	1271						
122°F	8880	7060	2.04	1276						

**LEGEND: W - Watts**  
**DB - Dry Bulb**  
**TC - Total Capacity**  
**SHR - Sensible Heat Ratio**  
**COP - Coefficient of Performance**

## FEATURES & FUNCTIONS SUMMARY


3VIR12HP115V1AO / 3VIR12HP115V1AH

### SYSTEM FEATURES


Inverter Type	G10
Ultra Low Frequency Torque Control	Yes
Power Factor Correction	Yes
Compressor Type - Inverter	High Efficiency Rotary
Basepan With Electric Heater	Yes
Indoor & Outdoor Fin Coating (Blue Fin)	Yes
Intelligent Defrosting	Yes
Intelligent Preheating	Yes
Low Voltage Startup	Yes
Memory/Power Failure Recovery	Yes
Self Diagnosis	Yes
Wired Controller Interface (XE71 or XK76 optional)	Yes
WiFi Included	Yes
<b>NEW! Easy Service Access</b>	Yes
Indoor Fan Type	Crossflow
Multi Fan Speeds	7 Speeds
Indoor Unit Display	Yes
Auxiliary Electrical Heater	No
Ventilation (Outdoor Air)	No




### REMOTE CONTROLLER FUNCTIONS

<b>NEW! Auto Clean</b>	Yes
Auto Mode	Yes
Auto Fan	Yes
Auto Swing (Horizontal Auto Swing)	Yes
Auto Swing - 180° (Vertical Auto Swing)	Yes
Clock	Yes
Dry Mode	Yes
Dry Anti-Mildew (X-Fan) Mode	Yes
Energy Saving Mode	Yes
Dirty Filter Alert	No
Fan Speed Control (7 Speeds)	Yes
I Feel Function	Yes
Privacy Lock	Yes
Quiet Mode	Yes
Room Temperature Display	No
Sleep Mode	Yes
3 Sleep Mode Options	Yes
Timer Mode	Yes
Turbo Mode	Yes
Display On/Off Control	Yes
Freeze Guard Mode	Yes
Power Failure Mode	Yes




Dimensions	
W	32 1/2
D	7 3/4
H	11 1/2
W1	4 7/16
W2	21 3/8
W3	6 11/16





Dimensions	
A	30 3/4
B	33 3/8
C	23 1/2
D	10 1/8
E	12 5/8
F	21 5/16
G	11 5/16

Unit: inch



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.